

FLP-12,5 V/4 S


Ordering number 8595090534303

SPD type 1 and type 2- Lightning Current Arrester and Surge Arrester


Four-pole varistor lightning current arrester, installation at the boundary of zones LPZ 0 and LPZ 1 or higher. Protection against impact of partial lightning currents, induced surge during a lightning strike or switching surges. For objects in LPL III and IV. Remote status signaling (S).



Dimension drawing



Basic circuit diagram



Technical specifications

Type of SPD	T1,T2
Nominal voltage	230 V AC
Maximum operating voltage	275 V AC
Maximum operating voltage	350 V DC
Lightning impulse current (10/350 µs)	12,50 kA
Nominal discharge current (8/20 µs)	30,00 kA
Maximum discharge current (8/20 µs)	60,00 kA
Voltage protection level at 5 kA	0,90 kV
Voltage protection level	1,20 kV
Short-circuit current rating	50,0 kA
Maximum overcurrent protection	160 A gL/gG
Response time	25 ns
TOV 5 s L-N	335 V
TOV characteristic (TOV 5 s)	withstand
Cross-section of connected conductors solid (min)	1,00 mm ²
Cross-section of connected conductors solid (max)	35,00 mm ²
Cross-section of connected conductors stranded (min)	1,00 mm ²
Cross-section of connected conductors stranded (max)	25,00 mm ²
Fault indication	red indication field
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC,250V/0,1A DC
Cross-section of remote indication conductors	1,5 mm ²
Degree of protection	IP 20
Range of operating temperatures - min	-40 °C
Range of operating temperatures - max	80 °C
Mounting	DIN rail 35 mm
According to standard	EN 61643-11:2012, IEC 61643-11:2011
Plug module	FLP-12,5 V/0
ETIM Class	EC001457