

SLP-275 V/1S+1


Ordering number 8595090524915

SPD type 2 - Surge Arrester


Combination of varistor surge arrester and encapsulated spark gap, connected in the 1+1 mode. Installation at the boundary of zones LPZ 1 and LPZ 2. Especially to sub-distribution boards in TT and also TN-C LV systems. Protection of the LV installations and equipments against induced surges and switching surge.
Remote status signaling (S).



Dimension drawing



Basic circuit diagram



Technical specifications

Type of SPD	T2
Nominal voltage	U _n 230 V AC
Maximum operating voltage L-N	U _c 275 V AC
Maximum operating voltage N-PE	U _c 255 V AC
Nominal discharge current (8/20 µs) L-N	I _n 20,00 kA
Nominal discharge current (8/20 µs) N-PE	I _n 20,00 kA
Maximum discharge current (8/20 µs) L-N	I _{max} 40,00 kA
Maximum discharge current (8/20 µs) N-PE	I _{max} 40,00 kA
Voltage protection level at 5 kA L-N	U _p 0,90 kV
Voltage protection level mode L-N	U _p 1,35 kV
Voltage protection level mode N-PE	U _p 1,50 kV
Voltage protection level mode L-PE	U _p 1,50 kV
Ability to independently switch off the following current N-PE	I _f 0,1 kA
Short-circuit current rating	I _{SCCR} 50,0 kA
Maximum overcurrent protection	160 A gL/gG
Response time L-N	t _a 25 ns
Response time N-PE	t _a 100 ns
TOV 5 s L-N	335 V
TOV characteristic (TOV 5 s)	withstand
TOV 120 min L-N	440 V
TOV characteristic (120 min)	failure
TOV 200 ms L-PE	1 455 V
TOV 200 ms N-PE	1 200 V
TOV characteristic (TOV 200 ms)	withstand
Cross-section of connected conductors solid (min)	1,00 mm ²
Cross-section of connected conductors solid (max)	35,00 mm ²
Cross-section of connected conductors stranded (min)	1,00 mm ²
Cross-section of connected conductors stranded (max)	25,00 mm ²
Fault indication L-N	red indication field
Fault indication N-PE	no
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC, 250V/0,1A DC
Cross-section of remote indication conductors	1,5 mm ²
Degree of protection	IP 20

Range of operating temperatures - min	-40 °C
Range of operating temperatures - max	80 °C
Mounting	DIN rail 35 mm
According to standard	EN 61643-11:2012, IEC 61643-11:2011
Plug module	SLP-275 V/0
ETIM Class	EC000941